

ROCKCRETE EQUIPMENT'S ROCKCRETER TSL



Solutions for plastering, grouting & TSL



ROCKCRETE
EQUIPMENT (PTY) LTD

Overview

The Rockcrete TSL is a small compact Grout Pump.

- 👉 Easy to transport
- 👉 Easy to clean
- 👉 Simple to operate
- 👉 Low maintenance

Applications

- 👉 Thin Skinliners
- 👉 Grout pumping
- 👉 Self leveling screeds
- 👉 Plaster spraying



Solutions for plastering, grouting & TSL



ROCKCRETE
EQUIPMENT (PTY) LTD

Technical Specifications

Dimensions	Length	:	900mm
	Width	:	700mm
	Height	:	1200mm
	Weight	:	240kg

Rotor Stator D8 - 2	Pump capacity / output	:	Up to 1 cub m /hour
	Aggregate size	:	Up to 4mm
	Pressure	:	35 bar pumping pressure
	Conveying distance	:	Up to 30m [material dependant]

Drive Options	Air drive pump	:	Air Requirements 4 - 6 bar @ 400cfm
	Electric drive pump	:	3kW on pump, 0.75kW on mixer

Options	:	Variable speed
	:	External compressor
	:	External vibrator



Rockcrete Equipment (PTY) LTD
361 Crocker Road
Wadeville, Germiston 1428

Phone: +27 11 865 3019
Email: information@rockcrete.co.za
www.rockcrete.co.za