

ROCKCRETE EQUIPMENT'S ROCKCRETER HIGH SHEAR MIXER



Solutions for cementitious grout mixing



ROCKCRETE
EQUIPMENT (PTY) LTD

As part of our policy of constant product development and improvement, information and specifications contained in this document are liable to change

Last revised: May-2022

Overview

The colloidal mixer is particularly suitable for the consistent mixing of water, cement, bentonite and other fine materials. A robust mixing tank combined with highly wear resistant materials in the mixing pump guarantee a long service of life

Applications

- Preparation of suspensions consisting of water, cement, bentonite and other fine materials.
- As a stand alone unit or in combination with an agitator.



Solutions for cementitious grout mixing



ROCKCRETE
EQUIPMENT (PTY) LTD

Technical Specifications

Dimensions	Length	:	1000mm
	Width	:	950mm
	Height	:	1380mm
	Weight	:	±270kg

High shear mixer	Electric motor	:	7.5kW
	Mixing capacity	:	250Ltr
	Rotation speed	:	1450Rpm
	Internal Flow Speed	:	900Ltr/min
	Approx Capacity	:	5cub m/hour
	Water connection	:	1" Bsp
	Liquid temp	:	Max 40°C

Drive Options	Electric drive pump	:	7.5kW / 380 V or 525V
----------------------	---------------------	---	-----------------------



Rockcrete Equipment (PTY) LTD
361 Crocker Road
Wadeville, Germiston 1428

Phone: +27 11 865 3019
Email: information@rockcrete.co.za
www.rockcrete.co.za